

BEAUTIFY YOUR HOME BY USING



KALSOMINE

A DRY POWDER WHICH IS READY
FOR USE WHEN MIXED WITH
COLD WATER.

Sanitary, Beautiful & Durable Finish

MANUFACTURED BY
COLORO COMPANY Pty. Ltd.
PORT MELBOURNE.

101				110
102		119		111
103		ALWAYS ORDER BY NUMBERS.		112
104				113
105				114
106				115
107				116
108		120		117
109				118

COLO KALSOMINE

DIRECTIONS.

Add sufficient cold water to Colo Kalsomine dry powder to make a thick paste, not too stiff for stirring. When all lumps have been thoroughly broken up, add cold water to make it spread well, and it is ready for immediate use.

Do not apply over loose and scaly distempers.

Colo Kalsomine is a perfect primer and filler for woodwork, which gives better results than oil priming, and prevents blistering.

Colo Kalsomine can be used on all surfaces, such as wood, plaster, paper, bricks, etc.

Clean off all dirt on old distempers before applying Colo Kalsomine.

Stop cracks, etc., by mixing Colo Kalsomine into stiff putty, which will not catch up like plaster of Paris when gone over with Kalsomine.

To walls, etc., having much suction, size with Miluco Size and Turps, by dissolving Miluco Clear Blue Size in boiling water, and adding half a pint of Turps (use cold), leaving dry before coating with Kalsomine.

Colo Kalsomine gradually thickens or jells after being mixed, and does not need more water unless it drags over the work.

Colo Kalsomine can be Varnished by dissolving one part of Miluco Size in six parts of boiling water. When cold apply to surface. When dry can be varnished.

CAUTION—See that the Size is not too strong and that the whole of the surface is covered previous to varnishing.

Colo Kalsomine for interior ceilings and walls is easy spreading, and has good covering qualities, which insures good results for artistic work and plain tinting.

Colo Kalsomine covers well with one coat, and can be recoated if necessary.

Colo Kalsomine is put up in 5-lb. packets, and one packet will cover 30 to 40 square yds.

Recno 61361